

Rockfon® Education Plus™



Features & Benefits

- Designed to enhance learning spaces with its smooth white surface that brightens classrooms and aids concentration
- High NRC of 0.80 creates a quieter, more focused educational setting, ideal for improving speech intelligibility
- Achieves Class A fire performance
- Available in both square lay-in and tegular edge designs
- Compliant with the Build America, Buy America Act (BABAA)

Applications

- Classroom
- Private Office
- Meeting Room



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance




Smooth, Modern Aesthetics



Mold and Mildew Resistance



30-year Warranty Applies to All Stone Tiles and Panels





High Performance Factors

Base Material	Stone Wool			Mold & Mildew Resistance	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
Surface	Smooth				
Fire Performance	Class A			Sag Resistance	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
	Tested to US Standard ASTM E84:	Flame Spread Index: 0 Smoke Developed Index: 5			
	Canadian Standard CAN/ULC S102:	Flame Spread Index: 5 Smoke Developed Index: 0			
Warranty	30-Year Tile Warranty			Low VOC	UL GREENGUARD Gold Certified



Standard Panels









Edge Designation	Item Number	Modular Size (nominal)	NRC	CAC	Fire Class	Mold & Mildew Resistance	Sag Resistance (relative humidity)	Light Reflectance	Embodied Carbon		Low VOC	Recyclable	lbs/sqft	sqft/carton
									Per 1m² (kg CO₂ - eq)	Per 1ft² (kg CO₂ - eq)				
 Square Lay-In	42100	2' x 2' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.45	80
	42101	2' x 4' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.45	80
 Square Tegular Narrow	42200	2' x 2' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.57	40
	42201	2' x 4' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.57	80
 Square Tegular	42300	2' x 2' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.57	40
	42301	2' x 4' x 3/4"	0.80	20	A	✓	up to 100%	0.82	2.96	0.275	✓	✓	0.57	80

Product Compatibility

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4500, 4600 and Fire Rated systems
 Square Lay-In Square Tegular	 SQ - Square Lay-In (2' x 2' & 2' x 4' only) SLN - Square Tegular Narrow 4000 - Tempra 4500 - Ultraline 1/4" reveal 4600 - Ultraline 1/8" reveal

Rockfon® Education Plus™

Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		250348	935.00	Universal Hold Down Clip	1000	16
		237949	490.00	Hold Down Clip for 0" - 3/4" Panels (Black)	100	2
		237952	491.00	Hold Down Clip for 3/4" - 1-1/4" Panels (Blue)	150	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15
Tile Paint		307988	RFN941	Edge Paint for Field Cut Panels White – 8 oz	Bottle	1
		307989	RFN941Q	Edge Paint for Field Cut Panels White – 32 oz	Can	1

*Clips should be chosen as per tile thickness

Scan for Full Accessories Guide



Rockfon® Education Plus™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied water-based paint on glass scrim surface.



ASTM E1264 Classification

ASTM E1264 (2022): Type IV, Form 3, Pattern G
ASTM E1264 (2023): Type A, Form A2.3, Pattern G



Fire Performance

Rockfon® Education Plus™ tiles are tested for Surface Burning Characteristics to UL 723 (ASTM E84) for the US and CAN/ULC-S102 for Canada, and achieve:

Tested to US Standard Flame Spread Index: 0
UL 723 (ASTM E84): Smoke Developed Index: 5

Canadian Standard Flame Spread Index: 5
CAN/ULC S102: Smoke Developed Index: 0



Mold and Mildew Resistance

Stone wool is inherently resistant to mold and mildew without added antimicrobials. Both, tile surface and substrate, are tested to:

✓ ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings)

✓ ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings)



Humidity Resistance

Stone wool ceiling tiles are inherently humidity resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity



Cleaning

✓ Vacuum



Thermal Resistance

R 2.60 hr.°F/Btu for 3/4 inch (I-P)
R 0.46 m².K/W for 19.0 mm (SI)



Tile Directionality

Rockfon® Education Plus™ tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°



Warranty

30-Year Limited Product Warranty.
See rockfon.com

Sustainability



Transparency

- ✓ Environmental Product Declaration (Product-Specific, Type III)
- ✓ Health Product Declaration
- ✓ Declare Label

Applicable to all edge types



Low-Emitting Materials

UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments.



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3 for SQ Edge: 2.96 kg CO₂-eq (per 1m²) * / 0.2.75 kg CO₂-eq (per 1f²)

For all other edge types, refer to p. 2



Rockcycle - Closed Loop Recycle Program

All stone wool ceiling tiles are eligible for the Rockcycle program. Please contact rockcycle@rockfon.com for more information



Discover Rockfon® Education Plus™

on Ecomedes and see how it aligns with the Common Materials Framework (CMF)

Find us on

MasterSpec®
Powered by Delttek Specpoint®

BIM/Revit objects available at:

rockfon.com/products/tiles-and-panels/modular-ceilings/special-applications/education/rockfon-education-plus/