

Rockfon® Contour™ Baffle

Features & Benefits

- Innovative and aesthetically pleasing frameless acoustical baffles in smooth matte White finish
- Quick and easy to install
- Variety of rectangular and wave shapes offer versatility in architectural designs
- Use alone or in combination with an existing acoustic ceiling to enhance the sound absorption
- Rockfon® Contour™ baffles are UL GREENGUARD certified for low chemical emissions to support overall indoor air quality

Applications

- Education
- Retail
- Healthcare
- Office
- Leisure
- Open Plan Space



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics



Mold and Mildew Resistance




30-year Warranty Applies to All Stone Tiles and Panels



Rockfon® Contour™ Baffle

Rockfon Contour™ stone wool acoustical frameless baffles unite form and function. These elegant baffles offer fast and hassle-free installation, blending into any ceiling design. Contour allows designers to create waves, shapes, or a sleek linear look, adding artistry to ceilings and setting a new standard for performance, aesthetics, and versatility.



Scan to explore Rockfon® Contour™ Baffle

Sustainability Certifications and Documentation


High Performance Factors

Base Material	Stone Wool
Surface	Smooth White
Fire Performance	Class A Tested to US Standard ASTM E84: Flame Spread Index: 0 Smoke Developed Index: 5 Canadian Standard CAN/ULC S102: Flame Spread Index: 5 Smoke Developed Index: 0
Mold and Mildew Resistance	Inherently Resistant Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Baffles Pass)
Low VOC	UL GREENGUARD Certified
Warranty	30-Year Warranty

Standard Panels








Packaging Information

Shape	Edge Designation	Item Number	Dimensions H x L x T (in)	Fire Class	Mold & Mildew Resistance	Low VOC	Recyclable	Light Reflectance	Embodied Carbon		lbs/pc	pcs/ ctn	Screw Eyes Included in the box (1 bag = screw eyes)
									Per 1m² (kg CO2 - eq)	Per 1ft² (kg CO2 - eq)			
<div>Rectangle</div> 	<div>SQe</div> 	363150	12" x 47.5" x 2"	A	✓	Y	✓	0.79	6.13	0.570	5	8	2 bags
		363146	24" x 47.5" x 2"	A	✓	Y	✓	0.79	6.13	0.570	9.5	4	1 bag
		363145	12" x 71" x 2"	A	✓	Y	✓	0.79	6.13	0.570	7	8	2 bags
		363136	24" x 71" x 2"	A	✓	Y	✓	0.79	6.13	0.570	14.5	4	1 bag
<div>Wave</div> 		363178	6"/12" x 47.5" x 2" Wave	A	✓	Y	✓	0.79	6.13	0.570	3.5	8	2 bags
		363198	12"/18" x 47.5" x 2" Wave	A	✓	Y	✓	0.79	6.13	0.570	6	4	1 bag
		363162	18"/24" x 47.5" x 2" Wave	A	✓	Y	✓	0.79	6.13	0.570	8.5	4	1 bag

Rockfon® Contour™ Baffles are not suitable for use above swimming pools or outdoors.
Rockfon® Contour™ Baffles are decorative acoustic products and not designed for impact resistance.

Rockfon® Contour™ Baffle

Accessories

Detail	Rockfon Part Number	Product Description	Packaging	
			Pcs/ Ctn	Lbs/ Ctn
	N/A	Steel Screw Eye (delivered along with the baffle) with 4.85 mm diameter	Delivered along with the baffles. The weight of anchor and screw eyes: 0.07 lb/baffle	
	N/A	Pre-embedded plugs		
	233139	Suspension Kit - Classic Solution 59" Long (The Rockfon® Contour™ Classic Suspension Kit can be secured using a standard setscrew that corresponds to the relevant soffit material (e.g. concrete, wood, etc.)	12	1.15
	233134	Suspension Kit - Design Solution 59" Long (The Rockfon® Contour™ Design Suspension Kit features a refined cylindrical capping that hides the screw thread and provides a visually appealing finish. It can be fastened using a standard set screw that corresponds to the relevant soffit material. Alternatively an M6 thread wire can be used.)	12	1.5
	470	Standard Eyelet Suspension Kit Adjustable 120" long metal wire kit.	10	1.12
	322149	Spacer	200 pcs / box	0.55

Scan for Full
Installation Guide




Rockfon® Contour™ Baffle

Acoustics

	Sabins of Sound Absorption per Rectangular Baffle						Array-NRC		
	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Row Spacing 12" O.C.	Row Spacing 18" O.C.	Row Spacing 24" O.C.
Rectangular 12" x 47.5" x 2"	0.7	1.5	3.6	5.4	5.0	4.0	1.00	0.70	0.50
Rectangular 12" x 71" x 2"	1.1	2.0	4.7	6.1	5.7	5.6	1.00	0.70	0.50
Rectangular 24" x 47.5" x 2"	1.7	2.8	5.4	6.6	6.0	5.8	1.35	0.90	0.70
Rectangular 24" x 71" x 2"	1.7	4.1	7.5	8.0	7.3	7.9	1.35	0.90	0.70

- Notes: 1. Sabins of Sound Absorption has been tested with baffles suspended 12" below reflective surface.
2. Array-NRC is calculated per ASTM C423-23 Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method, Appendix X2 Sound Absorption Ratings for Arrays of Spaced Objects.
3. Array-NRC relates to the overall absorption provided by an array of Baffles. To increase Array-NRC, decrease the space between Baffles or select taller Baffles. Array-NRC is not the NRC rating of the surface of an individual Baffle.
4. Array NRC values for 12" and 18" nominal row spacing are extrapolated from tests done on Baffles spaced 24" apart.
5. Dimensions are nominal. Contact Rockfon for actual sizes.




Rockfon® Contour™ Baffle

Acoustics

	Sabins of Sound Absorption per Wave Baffle						Array-NRC		
	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Row Spacing 12" O.C.	Row Spacing 18" O.C.	Row Spacing 24" O.C.
Wave 48" x 6/12" x 2"	0.6	1.2	2.9	4.7	4.5	3.4	0.85	0.60	0.40
Wave 48" x 12/18" x 2"	1.1	1.5	4.2	5.8	5.4	5.4	1.10	0.70	0.55
Wave 48" x 18/24" x 2"	1.2	1.4	5.2	6.3	6.0	5.8	1.30	0.85	0.65

- Notes: 1. Sabins of Sound Absorption has been tested with baffles suspended 12" below reflective surface.
2. Array-NRC is calculated per ASTM C423-23 Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method, Appendix X2 Sound Absorption Ratings for Arrays of Spaced Objects.
3. Array-NRC relates to the overall absorption provided by an array of Baffles. To increase Array-NRC, decrease the space between Baffles or select taller Baffles. Array-NRC is not the NRC rating of the surface of an individual Baffle.
4. Array NRC values for 12" and 18" nominal row spacing are extrapolated from tests done on Baffles spaced 24" apart.
5. Dimensions are nominal. Contact Rockfon for actual sizes.



Rockfon® Contour™ Baffle Properties

Material

Stone wool (Mineral Wool) frameless baffle with factory applied water-based paint on glass scrim surface on both sides of baffle.



ASTM E1264 Classification

ASTM E1264 (2022) : Type IV, Form 3, Pattern G
ASTM E1264 (2023): Type A, Form A2.3, Pattern G



Warranty

30-Year Limited Product Warranty.
See rockfon.com



Fire Performance

Rockfon® Contour™ Baffles are tested for Surface Burning Characteristics to UL 723 (ASTM E84) for the US and CAN/ULC-S102 for Canada, and achieve:

Tested to US Standard Flame Spread Index: 0
UL 723 (ASTM E84): Smoke Developed Index: 5

Canadian Standard Flame Spread Index: 5
CAN/ULC S102: Smoke Developed Index: 0



Mold and Mildew Resistance

Stone wool is inherently resistant to mold and mildew without added antimicrobials. Both, tile surface and substrate, are tested to:

- ✓ ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings)
- ✓ ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings)



Humidity Resistance

Stone wool is inherently humidity resistant



Cleaning

- ✓ Vacuum

Sustainability



Transparency

- ✓ Environmental Product Declaration (Product-Specific, Type III)



Low-Emitting Materials

UL GREENGUARD certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3:
6.13 kg CO₂-eq (per 1m²) / 0.570 kg CO₂-eq (per 1ft²)



Rockcycle - Closed Loop Recycle Program

All stone wool ceiling tiles are eligible for the Rockcycle program. Please contact rockcycle@rockfon.com for more information



Discover Rockfon® Contour™ Baffle

on Ecomedes and see how it aligns with the Common Materials Framework (CMF)

Find us on

MasterSpec®
Powered by Deltek Specpoint®

BIM/Revit objects available at:
rockfon.com/products/rockfon-contour/